

## VRLA Compliance Package

Economy



This room contains energized battery systems.  
Battery electrolyte solutions may be corrosive.



24/7 FSD CONTACT INFO

NAME:  
CONTACT IN CASE OF AN EMERGENCY  
NUMBER:



BATTERY ELECTROLYTE SOLUTION MAY BE CORROSIVE

HYDROGEN GAS MAY BE EXPLOSIVE

FIRE HAZARD PRESENT



VRLA BATTERY SYSTEM

HIGH VOLTAGE

VOLTS, AMPS

Part Number: COMPECO-VRLA

### Features

- **SCK-5** - Complies with Fire Codes, Building Codes, and OSHA 1910.178. High-density polyethylene container with ribbed reinforcement for strength. Height: 14.5" Diameter: 11.25" Weight: 15.6 lbs.
- **SIGN-BTRM** - Complies with NFPA, IFC, OSHA and ANSI/IEEE. Viewing Distance 50 feet. Dimensions: 14" x 10" x 0.06"
- **NFR3** - Complies with NFPA, OSHA, Uniform Fire Code (ICBO) and National Fire Code (BOCA). Viewing Distance 50 feet. Dimensions: 14" x 10"
- **SIGNEYEWSH** - Emergency Eyewash Station Sign. Viewing Distance 50 feet. Dimensions: 14" x 10" x 0.06"
- **EYE-PR** - 2-32 oz. replaceable squeeze bottles. Wall mountable. Shipping weight 6.9 lbs.

### Part Number

COMPECO-VRLA

### Regulations In Compliance With

NFPA  
International Fire Code (IFC)  
National Fire Code (BOCA)  
OSHA  
ANSI / IEEE

### Recommended Training

Battery Room Compliance 101  
[www.enviroguarduniversity.com](http://www.enviroguarduniversity.com)